



D	F	I	H	H1	CH	P
6	1/8	8	31.5	19	12	3.5
7	1/8	8	31.5	19	12	4.5
8	1/8	8	31.5	19	12	5.5
9	1/8	8	31.5	19	12	6
10	1/8	8	32.5	20	12	7.5
7	1/4	11	35	19	14	4.5
8	1/4	11	35	19	14	5.5
9	1/4	11	35	19	14	6.5
10	1/4	11	36	20	14	7.5
12	1/4	11	36	20	14	9.5
9	3/8	11.5	35.5	19	17	6.5
10	3/8	11.5	36.5	20	17	7.5
12	3/8	11.5	36.5	20	17	9.5
14	3/8	11.5	38.5	22	17	11
10	1/2	14	39.5	20	22	7.5
12	1/2	14	39.5	20	22	9.5
14	1/2	14	41.5	22	22	11
17	1/2	14	43.5	24	22	13.5

Articolo:

260

PORTAGOMMA MASCHIO CONICO
HOSE CONNCTOR MALE
CONICAL

 **AIREX**[®]

CAMPI DI IMPIEGO: Circuiti pneumatici, oleodinamici e idraulici

MATERIALI IMPIEGATI: Ottone UNI EN 12164 CW 614N. Ottone UNI EN 12165 CW 617N. Guarnizione NBR

TRATTAMENTO SUPERFICIALE: Nichelatura

FILETTATURA: Gas conica ISO 7 – DIN 2999 – BS21.

APPLICATION FIELDS: Pneumatic, hydraulic and hydraulic circuits

MATERIALS USED: Brass UNI EN 12164 CW 614N. Brass UNI EN 12165 CW 617N. Gasket NBR

TREATMENT: Nickel Plating

THREAD: Conical gas ISO 7 - DIN 2999 - BS21.