



| Tubo | D1     | D2 | D3   | L1  | L2   | CH1 | CH2 | gr.  |
|------|--------|----|------|-----|------|-----|-----|------|
| 3    | M3X0.5 |    |      |     |      |     |     |      |
| 3    | M5X0.8 |    |      |     |      |     |     |      |
| 4    | M5X0.8 | 9  | 8    | 4   | 19   |     | 2,5 | 4,6  |
| 6    | M5X0.8 | 12 | 8    | 4   | 22   |     | 2,5 | 8,6  |
| 4    | 1/8    | 9  | 13   | 5   | 16,5 | 9   | 3   | 6    |
| 6    | 1/8    | 12 | 13,5 | 5   | 19,5 | 12  | 4   | 9    |
| 8    | 1/8    | 14 | 13   | 5   | 23,5 | 13  | 6   | 11,5 |
| 4    | 1/4    | 9  | 16   | 6,5 | 18,5 | 9   | 3   | 12   |
| 6    | 1/4    | 12 | 16   | 6,5 | 19,5 | 12  | 4   | 12,7 |
| 8    | 1/4    | 14 | 16   | 6,5 | 21,5 | 14  | 6   | 13,5 |
| 10   | 1/4    | 16 | 16   | 6,5 | 27,5 | 15  | 8   | 17,4 |
| 8    | 3/8    | 14 | 20   | 7   | 21   | 14  | 6   | 20,1 |
| 10   | 3/8    | 16 | 20   | 7   | 25   | 16  | 8   | 22,6 |
| 12   | 3/8    | 19 | 20   | 7   | 28,5 | 19  | 10  | 29   |
| 12   | 1/2    | 19 | 25   | 8,5 | 26,5 | 19  | 10  | 36,1 |

Articolo:

351Z

RACCORDO DIRITTO MASCHIO  
CILINDRICO  
CYLINDRICAL MALE STRAIGHT  
FITTING

**AIREX®**

**CAMPI DI APPLICAZIONE:** impianti pneumatici

**MATERIALI:** ottone UNI EN 12164 CW 614 N. Ottone UNI EN 12165 CW 617 N. Nichelato

**FILETTATURE:** coniche pretefalonate.

**APPLICATION FIELDS:** pneumatic plants

**MATERIALS:** brass UNI EN 12164 CW 614 N. Brass UNI EN 12165 CW 617 N. Nickel-plated

**THREADS:** pre-teflon coated conical.