



Tubo	D1	D2	L1	L2	CH	gr.
4	1/8	9	7,5	16	10	5,5
4	1/4	9	11	20,5	14	16,1
6	1/8	12	7,5	21	12	8,7
6	1/4	12	11	20,5	14	14
8	1/8	14	7,5	25	14	13,2
8	1/4	14	11	23,5	14	13,9
8	3/8	14	11,5	22,5	17	23,6
10	1/4	16	11	30,5	16	20,2
10	3/8	16	11,5	24	17	20,6
10	1/2	16	14	27	22	47,5
12	1/4	19	11	32	19	24
12	3/8	19	11,5	27,5	19	24,1
12	1/2	19	14	27,5	22	42,3
14	1/2	22	14	32,5	22	39,5
14	3/8				22	

Articolo:

351

RACCORDO DRITTO MASCHIO
CONICO
STRAIGHT MALE CONICAL FITTING

AIREX®

CAMPI DI APPLICAZIONE: impianti pneumatici

MATERIALI: ottone UNI EN 12164 CW 614 N. Ottone UNI EN 12165 CW 617 N. Nichelato

FILETTATURE: coniche pretefalonate.

APPLICATION FIELDS: pneumatic plants

MATERIALS: brass UNI EN 12164 CW 614 N. Brass UNI EN 12165 CW 617 N. Nickel-plated

THREADS: pre-teflon coated conical.