

6.2.2.2 Sicurezza



							Nº
340 – 600	490	160	250	–	–	Roto Sil	2005271
601 – 800	690	200	350	–	–	Roto Sil	2005272
801 – 1000	890	200	500	1	V	Roto Sil	2005276
1001 – 1200	1090	200	500	1	V	Roto Sil	2005277
1201 – 1400	1290	200	500	1	V	Roto Sil	2005278

In caso di PA > 150 kg, la guida articolazione 500 deve essere fissata con la piastrina di supporto 255211.

6.2.2.3 Anta a ventola



					Nº
411 – 600	490	150	250	Roto Sil	2005279
511 – 710	600	200	250	Roto Sil	2005280



INFORMAZIONI

Utilizzabile solo in combinazione con l'asta leva standard.




INFORMAZIONI

Da LBB 711 mm è necessaria la chiusura centrale.

6.2.3 Lato cerniera Designo (AF 9 / AF 13)

6.2.3.1 Sicurezza base



								Nº
330 – 600	490	170	250	–	–	Sicurezza antichiusura	Roto Sil	385393
601 – 800	690	200	350	–	–	–	Roto Sil	385394
801 – 1000	890	200	500	1	E	–	Roto Sil	385415
1001 – 1200	1090	200	500	1	E	–	Roto Sil	385416