



2.2.1.3 4 nottolini V (4V) – agganciabili in alto



1900 – 2200	28	92	8	1020	STI ZOV	300	V22/25	H650	Roto Sil	5 Pezzo/-i	2003461	
	45	92	8	1020	STI ZOV	300	V22/25	H650	Roto Sil	5 Pezzo/-i	2003462	
	50	92	8	1020	STI ZOV	300	V22/25	H650	Roto Sil	5 Pezzo/-i	2003463	
1915 – 2165	25	92	8	1020	ZOV	300	V18/25	H650	Roto Sil	5 Pezzo/-i	2003442	
	28	92	8	1020	ZOV	300	V18/25	H650	Roto Sil	5 Pezzo/-i	2003443	
	35	92	8	1020	ZOV	300	V18/25	H650	Roto Sil	5 Pezzo/-i	2003444	
	45	92	8	1020	ZOV	300	V18/25	H650	Roto Sil	5 Pezzo/-i	2003445	
	55	92	8	1020	ZOV	300	V18/25	H650	Roto Sil	5 Pezzo/-i	2003446	

Idoneo incontro a puntale sopra: incontro a puntale 110 con invertitore → *da pagina 190*



INFORMAZIONI

Nelle serrature multipunto con la caratteristica “versione speciale STI” l’incontro a puntale è integrato in basso.



INFORMAZIONI

Selezionare il disegno dimensionale dettagliato della serratura multipunto mediante lo schema di posizionamento incontri → *da pagina 312*.

Elementi di collegamento



2200 – 3000	200	F16	–	–	–	–	Roto Sil	10 Pezzo/-i	633956	
			–	–	1	V	Roto Sil	10 Pezzo/-i	637588	
		F20	–	–	–	–	Roto Sil	10 Pezzo/-i	633957	
			–	–	1	V	Roto Sil	10 Pezzo/-i	637589	
	400	F16	–	–	–	–	Roto Sil	10 Pezzo/-i	633934	
			–	–	1	V	Roto Sil	10 Pezzo/-i	637587	
		F20	–	–	–	–	Roto Sil	10 Pezzo/-i	633955	
			–	–	1	V	Roto Sil	10 Pezzo/-i	637590	



INFORMAZIONI

ABB massima 3000 mm: si possono accoppiare due elementi di collegamento di lunghezza 200 mm o 400 mm.