

SCHEDA TECNICA

PARIDE

SECUREMME®

SERRATURA APPLICARE BLINDATI SERIE 140C SECUREMME
A DOPPIA MAPPA TRIPLICE CHIUSURA

FISSAGGIO PLANARE | PLANAR FIXING

| 3+1T chiavi 3+1T keys |  g | 5+1T chiavi 5+1T keys |  g | Sporgenza pistoncini (S) Projection bolts (S) | Interspazio Interspace |  |  |
|--------------------------|---|--------------------------|---|--|---------------------------|---|---|
| 140 1 SCR0328S56 | 2260 | - | - | 3 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR0337S56 | 2170 | - | - | 3 mm | 37 mm | 50 mm | 5 |
| 140 1 SCR0628S56 | 2280 | - | - | 6 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR0637S56 | 2190 | - | - | 6 mm | 37 mm | 50 mm | 5 |
| 140 1 SCR1328S56 | 2340 | - | - | 13 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR1337S56 | 2250 | - | - | 13 mm | 37 mm | 50 mm | 5 |
| 140 1 SCR2328S56 | 2420 | - | - | 23 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR2337S56 | 2330 | - | - | 23 mm | 37 mm | 50 mm | 5 |
| 140 1 SCR3328S56 | 2500 | - | - | 33 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR3337S56 | 2410 | - | - | 33 mm | 37 mm | 50 mm | 5 |
| 140 1 SCR4328S56 | 2580 | - | - | 43 mm | 28 mm | 50 mm | 5 |
| 140 1 SCR4337S56 | 2490 | - | - | 43 mm | 37 mm | 50 mm | 5 |

