

Inserti filettati RIVSERT zigrinati

RIVSERT knurled rivet nuts

FRC-Z

34022

■ Acciaio



Steel

Fusto cilindrico zigrinato aperto

Open knurled cylindrical shank

Testa ridotta

Reduced head



d		T	k	SS	L	L ₂	Tipo	Codice		
mm	mm	mm	max	mm	mm	min ÷ max	Model	Item code	pz	pz
M3	5.0	5.5	0.3	0.5 ÷ 2.0	9.0	5.5 ÷ 6.5	FRCZ0302005	3394700	1000S	20000
				2.0 ÷ 3.5	11.5		FRCZ0303505	0321000		
M4	6.0	7.0	0.5	0.5 ÷ 2.0	11.0	6.5 ÷ 7.0	FRCZ0402006	2673800	1000N	16000
				2.0 ÷ 4.0	13.0		FRCZ0404006	3498900		
M5	7.0	8.0	0.5	0.5 ÷ 3.0	11.5	7.5 ÷ 8.0	FRCZ0503007	2232600	1000N	10000
				1.5 ÷ 3.5	13.0		FRCZ0503507	4300000		
				2.5 ÷ 5.0	15.0		FRCZ0505007	3466700		
M6	9.0	10.0	0.5	0.5 ÷ 3.0	14.0	8.5 ÷ 9.5	FRCZ0603009	1962000	500N	5000
				3.0 ÷ 5.0	17.5		FRCZ0605009	3348400		
M8	11.0	12.0	0.5	0.5 ÷ 3.0	16.5	10.0 ÷ 11.5	FRCZ0803011	1831600	250N	3000
				3.0 ÷ 5.0	18.5		FRCZ0805011	2806900		
M10	12.0	13.3	0.8	0.8 ÷ 3.5	19.5	11.0 ÷ 13.0	FRCZ1003512	4312600	200N	1500
				4.0 ÷ 6.5	24.0		FRCZ1006512	4512900		
M10	13.0	14.0	0.8	1.0 ÷ 3.5	20.5	12.0 ÷ 13.0	FRCZ1003513	3015900	200N	1500
				3.0 ÷ 6.0	22.0		FRCZ1006013	3348500		
M12	16.0	18.0	1.0	1.0 ÷ 4.0	24.0	13.5 ÷ 14.3	FRCZ1204016	3751300	100N	1000



Applicazione

Application

Carico di prova
assiale del filetto
Axial proof load
for thread



Coppia
di serraggio
Clamping
torque



Coppia di serraggio
per la forza di torsione
Clamping torque
for the torque force



Resistenza
al taglio
Shearing
strength



d			N	Nm	Nm	N
mm		mm				
M3		5.0	3900	1.0	0.4	900
M4		6.0	6800	4.0	0.8	1500
M5		7.0	11500	8.0	1.5	2000
M6		9.0	16500	15.0	3.5	3000
M8		11.0	25000	26.0	4.5	4400
M10		12.0	32000	45.0	8.5	5000
M10		13.0	32000	45.0	8.5	5000
M12		15.0	34000	70.0	24.0	6500