

Product data sheet for uvex profastrong NF34



Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
 Elso-Klöver-Str. 6
 D-21337 Lüneburg
 uvex-safety.de

uvex profastrong NF34 A sensitive, flexible NBR chemical protection glove with cotton flocking. It is characterised by its excellent mechanical abrasion resistance and very good grip in damp and wet areas. Impressive resistance to a range of oils, greases, acids and alkalis. High tactility and a perfect tactile feel.

Features

- Good mechanical abrasion resistance
- Good grip, even in wet work environments
- Extremely flexible
- Good fit

Material number	60719
Sizes	7,8,9,10,11
Standard	EN ISO 21420:2020, EN 388:2016 + A1:2018, EN ISO 374-1:2016 + A1:2018, EN ISO 374-5:2016, ISO 18889:2019
Standard	EN 388:2016 + A1:2018: 4101X, EN ISO 374-1:2016 + A1:2018: AJKLOPT, EN ISO 374-5:2016: bac/fungi/virus, ISO 18889:2019: G2
Test chemicals	Methanol (A), n-Heptane (J), Sodium hydroxide 40% (K), Sulphuric acid 96% (L), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)
Performance classes in accordance with EN 388	4 1 0 1 X
Outer material	Cotton-flocked
Coating	NBR
Coating surface area	Fully coated
Coating thickness	0.40 mm
Type	With gauntlet
Colour	Green
Glove length	33 cm