

### Product data sheet uvex silv-Air 2310 FFP3 NR D



# **Product information**

<ul> <li>Product         <ul> <li>Particle-filtering cup shape mask with exhalation valve</li> <li>Protection level FFP3</li> <li>Soft material edges for more high wearing comfort</li> <li>4-point headband attachment allows an individual and secure fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> <li>Flexible and adjustable nose clip</li> </ul> </li> </ul>	
<ul> <li>Soft material edges for more high wearing comfort</li> <li>4-point headband attachment allows an individual and secure fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> </ul>	
<ul> <li>4-point headband attachment allows an individual and secure fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> </ul>	
<ul> <li>fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> </ul>	
<ul> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> </ul>	
heat and moisture in the mask	
Flexible and adjustable nose clip	
Compatible with uvex safety eyewear	
Soft sealing lip guarantees a secure, comfortable sealed	
position of the mask	
Mask fulfils the requirements of the dolomite dust test (D)	
Materials Headband: textile	
Nose clip: aluminum	
Headband clips: PP	
Filter / mask: Melt Blown PP, Polyester	
Sealing lip: PVC foam	
Valve: ABS	
Weight 29 g	
Standard EN 149:2001 + A1:2009	

## Versions

Article number	Colour/Version	Retail unit
8732.310	cup shape mask FFP3, white with valve	15 pcs. per box
8752.310	cup shape mask FFP3, white with valve	3 pcs. per bag
8752.311	cup shape mask FFP3, white with valve	2 pcs. per bag

#### **Packaging sizes**

Box	approx. 260 x 140 x 180 mm
Outer Carton	approx. 570 x 550 x 290 mm

#### Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30l/min.	95l/min.	160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

### Areas of use\*

The respiratory protection mask can be used against solid, aqueous and non- volatile liquid aerosols up to <b>30 times</b> the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses,
	bacteria, enzyme, nanoparticles.

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth